



**All Seasons Pools & Spas**  
3201 Kaliste Saloom Rd.  
Lafayette, LA 70508  
Phone: 337.983.0025  
Fax: 337.983.0338  
[www.allseasonspools.net](http://www.allseasonspools.net)

## BACKWASH INSTRUCTIONS

### **INDICATION OF BACKWASH NEEDED:**

PSI GAUGE REACHES 8 TO 10 PSI'S ABOVE WHAT IT STARTED AT WHEN PUMP WAS INITIALLY TURNED ON. FILTER NEEDS TO BE BACKWASHED.

1. Turn pump off.
2. Attach backwash hose to backwash port on filter or roll out hose.
3. Turn filter to backwash position.
4. Turn pump on.
5. Watch water at end of backwash hose until it runs clear.
6. Turn pump off.
7. Turn filter to filter to waste position, or rinse position.
8. Turn pump on.
9. Count to 10. Steps 7, 8 & 9 are to keep any left over debris from going back in to pool after backwashing.
10. Turn pump off.
11. Turn filter to filter position.
12. Turn pump on and filter normal recommended hours.
13. Roll up backwash hose. You can leave hose attached to backwash port just roll it up.

### **Reminders:**

1. Clean sand with filter cleaner three times a year, Memorial Day, Fourth of July, and Labor Day. (Ask us how.)
2. Sand needs to be changed every 2 to 3 years. And the Spider Gasket in the valve head needs changed. Ask us how!
3. You can hard plumb your filter system; we have kits & shut off valves to make it easy. (Ask us how!)